

E-Cigarette Aerosol Analysis Report

Report No. : TCT210129C017

Date : Feb. 03, 2021

Page No.: 1 of 6

Applicant: Shenzhen Geekvape Technology Co., Ltd
Address: 7th Floor,#3 west Block, LaoBing Building, XingYe Rd#3012, Bao'an District, Shenzhen, Guangdong, China

The following sample was submitted and identified by/on behalf of the client as:

Sample Name: Obelisk 200 Kit
Model No.: Obelisk 200 Kit
MOD: 5-200W
Tank: 5.5ml
Coil: 1: MESH Z1: 0.4ohm KA1(50-60W) 2:MESH Z2: 0.2ohm KA1(70-80W)
Power level in testing: 1: 60 W 2: 80 W
Adjustable air inlet or not: Yes
Trade Mark: GEEKVAPE
Sample Received Date: 2021.01.29
Testing Period: 2021.01.29-2021.02.03
Test Method: Please refer to the following page(s).
Test Result(s): Please refer to the following page(s).

Test Items		Test Requested
1	Carbonyl Compounds: Formaldehyde, Acetaldehyde, Acrolein, Crotonaldehyde	Emission testing according to
2	Metals: Aluminum, Chromium, Iron, Nickel, Tin, Lead, Cadmium, Arsenic, Antimony	Article 20 of Tobacco Product
3	Nicotine consistency	Directive (2014/40/EU)

Checked by



Sin Lu

Signed for and on behalf of TCT

Noel Yin
Technical Manager

E-Cigarette Aerosol Analysis Report

Report No. : TCT210129C017

Date : Feb. 03, 2021

Page No.: 2 of 6

Test Results:

Test Condition for test items except Nicotine consistency test:

With reference to the CORESTA RECOMMENDED METHOD N° 81 method parameter, Afnor standardization XP D90-300-3, International Standard ISO 20768:2018 and PD CEN/TR 17236:2018, a smoke machine was used to collect the vapor.

Puff Duration	3.0s±0.1s
Puff Volume	55mL±0.3mL
Puff Frequency	30s±0.5s
Puff of Each Group	20
Group Interval Time	300s±120s
Maximum Flow	18.5mL/s±1.0mL/s
Pressure Drop	< 50hPa
Group	5
Total Number of Puff	100
Total Duration of Vaporization	300s

The temperature and relative humidity of the test atmosphere during machine preparation and testing were kept within the following limits: temperature $\pm 2^{\circ}\text{C}$, relative humidity $\pm 5\%$

Sample Description:

No.1 Obelisk 200 Kit with MESH Z1: 0.4ohm KA1(50-60W)

No.2 Obelisk 200 Kit with MESH Z2: 0.2ohm KA1(70-80W)

E-Cigarette Aerosol Analysis Report

Report No. : TCT210129C017

Date : Feb. 03, 2021

Page No.: 3 of 6

1. Carbonyl Compounds Content(s)

Method: The aerosol generated by the e-cigarette is absorbed by the impactor containing 40mL acidified solution of 2,4-dinitrophenylhydrazine (DNPH) in acetonitrile. The solution was filtered and analyzed by reverse phase high - performance liquid chromatography and determined using a UV detector.

Test Item	CAS No.	Unit	LOD	LOQ	Content(s)	
					No.1	No.2
Formaldehyde	50-00-0	ug/100puffs	0.667	2	81.5	28.4
Acetaldehyde	75-07-0	ug/100puffs	0.667	2	76.0	16.0
Acrolein	107-02-8	ug/100puffs	0.667	2	ND	ND
Crotonaldehyde	4170-30-3	ug/100puffs	0.667	2	ND	ND

- Note:
- ug = Microgram
 - ND = Not Detected (lower than LOD)
 - LOD = Limit of Detection
 - LOQ = Limit of Quantitation
 - E-Liquid Used: E-liquid B (AFNOR XP D90-300-3)

E-Cigarette Aerosol Analysis Report

Report No. : TCT210129C017

Date : Feb. 03, 2021

Page No.: 4 of 6

2. Metals Content(s)

Method: Wipe the clamp with isopropyl alcohol. Let stand for a minute. 20 ml of nitric acid was added to the impactor and placed in series with the Cambridge filter to absorb the aerosol. The Cambridge filter was removed and placed in nitric acid, shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by ICP-MS.

Test Item	CAS No.	Unit	LOD	LOQ	Content(s)	
					No.1	No.2
Aluminum(Al)	7429-90-5	ug/100puffs	0.025	0.25	ND	ND
Chromium(Cr)	7440-47-3	ug/100puffs	0.005	0.05	ND	ND
Iron(Fe)	7439-89-6	ug/100puffs	0.005	0.05	ND	ND
Nickel(Ni)	7440-02-0	ug/100puffs	0.025	0.25	ND	ND
Tin(Sn)	7440-31-5	ug/100puffs	0.25	2.5	ND	ND
Lead(Pb)	7439-92-1	ug/100puffs	0.025	0.25	ND	ND
Cadmium(Cd)	7440-43-9	ug/100puffs	0.005	0.05	ND	ND
Arsenic(As)	7440-38-2	ug/100puffs	0.025	0.25	ND	ND
Antimony(Sb)	7440-36-0	ug/100puffs	0.025	0.25	ND	ND

- Note:
- ug = Microgram
 - ND = Not Detected (lower than LOD)
 - LOD = Limit of Detection
 - LOQ = Limit of Quantitation
 - E-Liquid Used: E-liquid B (AFNOR XP D90-300-3)

E-Cigarette Aerosol Analysis Report

Report No. : TCT210129C017

Date : Feb. 03, 2021

Page No.: 5 of 6

3. Nicotine Consistency Test

Test Condition: With reference to the CORESTA RECOMMENDED METHOD N° 81 method parameter and Afnor standardization XP D90-300-3, a smoke machine was used to collect the vapor.

Puff Duration	3.0s±0.1s
Puff Volume	55mL±0.3mL
Puff of Each Group	20
Maximum Flow	18.5mL/s±1.0mL/s
Pressure Drop	< 50hPa

The temperature and relative humidity of the test atmosphere during machine preparation and testing were kept within the following limits: temperature $\pm 2^{\circ}\text{C}$, relative humidity $\pm 5\%$

Method: Wipe the clamp with isopropyl alcohol. Let stand for a minute. The aerosol generated by the e-cigarette is absorbed by the Cambridge filter. Remove the Cambridge filter and place it into a centrifuge tube, add 20 mL of Isopropyl alcohol and 0.2ml Internal standard stock solution. Shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by GC-FID.

Sample No.	Nicotine(CAS No.:54-11-5) Contents(mg/20Puffs)						Total (mg/100puffs)
	Group 1*	Group 2	Group 3*	Group 4	Group 5*	AVG	
No.1	5.23	5.29	5.16	5.25	5.19	5.23	26.1
Deviation(%)	0.0	-	1.2	-	0.6	-	-

Sample No.	Nicotine(CAS No.:54-11-5) Contents(mg/20Puffs)						Total (mg/100puffs)
	Group 1*	Group 2	Group 3*	Group 4	Group 5*	AVG	
No.2	4.64	4.64	4.66	4.64	4.60	4.64	23.2
Deviation(%)	0.1	-	0.5	-	0.7	-	-

- Note:
- mg = milligram
 - ND = Not Detected (lower than LOD)
 - LOD = Limit of Detection = 0.01mg/20Puffs
 - LOQ = Limit of Quantitation = 0.1mg/20Puffs
 - 1group = 20puffs
 - * Values used for determination of consistency of nicotine emission
 - E-Liquid Used: E-liquid A (AFNOR XP D90-300-3)
 - Under the conditions of the test and with reference to AFNOR XP D90-300-3, the electronic cigarette delivers a dose of nicotine at consistent levels.

E-Cigarette Aerosol Analysis Report

Report No. : TCT210129C017

Date : Feb. 03, 2021

Page No.: 6 of 6

Photo(s) of the sample(s)



Obelisk 200 Kit with MESH Z1: 0.4ohm KA1(50-60W)/ MESH Z2: 0.2ohm KA1(70-80W)

***** End of Report *****

Remark: This report is considered invalidated without the Special Seal for Inspection of the TCT. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of TCT, this test report shall not be copied except in full and published as advertisement.